



**otulina PE szara - TER MAX ST - odcinki 2mb**

średnica rury izolowanej		średn. wewn. otuliny [ mm ]	gr. izolacji 6mm		gr. izolacji 9mm	
[ cale ]	DN [ mm ]		cena [ zł / mb ]	opakowanie [ mb ]	cena [ zł / mb ]	opakowanie [ mb ]
---	---	12	0,90	600	1,19	450
1/4 "	10	15	1,01	500	1,47	350
3/8 "	12	18	1,21	420	1,60	320
1/2 "	15	22	1,30	350	1,74	260
3/4 "	20	28	1,62	250	2,01	200
1 "	25	35	1,97	200	2,41	150
1 1/4 "	32	42		---	2,89	100
1 1/2 "	40	48		---	3,48	90
---	---	54		---	7,24	70
2 "	50	60		---	7,60	60

**otulina PE czerwona - TER MAX PW - odcinki 2mb**

średnica rury izolowanej		średn. wewn. otuliny [ mm ]	gr. izolacji 6mm		gr. izolacji 9mm	
[ cale ]	DN [ mm ]		cena [ zł / mb ]	opakowanie [ mb ]	cena [ zł / mb ]	opakowanie [ mb ]
1/4 "	10	15	1,33	500	1,87	350
3/8 "	12	18	1,60	420	1,98	320
1/2 "	15	22	1,78	350	2,18	260
3/4 "	20	28	2,28	250	2,40	200
1 "	25	35	2,53	200	2,97	150

**otulina PE czerwona - TER MAX PWL - zwoje 10mb**

średnica rury izolowanej		średn. wewn. otuliny [ mm ]	gr. izolacji 4mm		gr. izolacji 6mm	
[ cale ]	DN [ mm ]		cena [ zł / mb ]	opakowanie [ mb ]	cena [ zł / mb ]	opakowanie [ mb ]
---	---	12	1,17	210	1,42	200
1/4 "	10	15	1,24	200	1,52	150
3/8 "	12	18	1,43	150	1,75	140
1/2 "	15	22	1,50	130	1,84	110
3/4 "	20	28	1,64	100	2,00	90
1 "	25	35	1,98	90	2,44	80